

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : SP Dry Erase Clear  
 Product code : 22833

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Polymeric US  
 117 East 14th Avenue  
 North Kansas City, MO 64116 - USA  
 T 816-221-5567

#### 1.4. Emergency telephone number

Emergency number : Chemtrec 800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H318 - Causes serious eye damage.  
 H351 - Suspected of causing cancer.  
 H361 - Suspected of damaging fertility or the unborn child.  
 H373 - May cause damage to organs through prolonged or repeated exposure.  
 H402 - Harmful to aquatic life  
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
 P261 - Avoid breathing vapours, spray, mist.

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms and face thoroughly after handling.  
 P272 - Contaminated work clothing must not be allowed out of the workplace  
 P273 - Avoid release to the environment.  
 P280 - Wear eye protection, protective gloves.  
 P302+P352 - If on skin: Wash with plenty of water/...  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P310 - Immediately call a poison center/doctor/...  
 P314 - Get medical advice/attention if you feel unwell.  
 P321 - Specific treatment (see supplemental first aid instruction on this label)  
 P332+P313 - If skin irritation occurs: Get medical advice/attention.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P363 - Wash contaminated clothing before reuse.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-phenoxyethyl acrylate	(CAS-No.) 48145-04-6	15 - 30	Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,6-hexanediol diacrylate	(CAS-No.) 13048-33-4	15 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
1-ethenyl-2-pyrrolidinone, inhibited	(CAS-No.) 88-12-0	10 - 15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 3, H402
trimethylolpropane triacrylate, stabilized	(CAS-No.) 15625-89-5	2 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
benzophenone	(CAS-No.) 119-61-9	1 - 2	Carc. 2, H351
TPO	(CAS-No.) 75980-60-8	1 - 2	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
 First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
 First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
 Symptoms/effects after eye contact : Serious damage to eyes.

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

trimethylolpropane triacrylate, stabilized (15625-89-5)		
Not applicable		
1,6-hexanediol diacrylate (13048-33-4)		
Not applicable		
1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)		
ACGIH	Local name	N-Vinyl-2-pyrrolidone
ACGIH	ACGIH TWA (ppm)	0.05 ppm
ACGIH	Remark (ACGIH)	Liver dam
ACGIH	Regulatory reference	ACGIH 2018

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### benzophenone (119-61-9)

Not applicable

### TPO (75980-60-8)

Not applicable

### 2-phenoxyethyl acrylate (48145-04-6)

Not applicable

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

## 8.3. Individual protection measures/Personal protective equipment

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : Colourless  
Odour : acrylate odor  
Odour threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : > 212 °F  
Relative evaporation rate (butylacetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapour pressure : No data available  
Relative vapour density at 20 °C : No data available  
Relative density : No data available  
Solubility : No data available  
Log Pow : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive limits : No data available  
Explosive properties : No data available  
Oxidising properties : No data available

### 9.2. Other information

No additional information available

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

<b>trimethylolpropane triacrylate, stabilized (15625-89-5)</b>	
LD50 oral rat	5190 mg/kg (Rat, Oral)
LD50 dermal rabbit	5170 mg/kg (Rabbit, Dermal)
ATE US (oral)	5190 mg/kg bodyweight
ATE US (dermal)	5170 mg/kg bodyweight
<b>1,6-hexanediol diacrylate (13048-33-4)</b>	
LD50 oral rat	> 5000 mg/kg (Rat, Oral)
LD50 dermal rabbit	3600 mg/kg (Rabbit, Dermal)
ATE US (dermal)	3600 mg/kg bodyweight
<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
LD50 oral rat	1022 mg/kg 834-1314,Rat; Equivalent or similar to OECD 401; Experimental value
LD50 dermal rat	1043 mg/kg rat
LD50 dermal rabbit	> 400 mg/kg (BASF test, 24 h, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	3.07 mg/l (BASF test, 4 h, Rat, Male/female, Experimental value, Inhalation (aerosol))
ATE US (oral)	1022 mg/kg bodyweight
ATE US (dermal)	1043 mg/kg bodyweight
ATE US (vapours)	3.07 mg/l/4h
ATE US (dust,mist)	3.07 mg/l/4h
<b>benzophenone (119-61-9)</b>	
LD50 oral rat	> 10000 mg/kg (Rat)
LD50 dermal rabbit	3535 mg/kg (Rabbit)
ATE US (dermal)	3535 mg/kg bodyweight
<b>TPO (75980-60-8)</b>	
LD50 oral rat	> 2000 mg/kg (Rat; Literature)
<b>2-phenoxyethyl acrylate (48145-04-6)</b>	
LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral, 14 day(s))

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
IARC group	3 - Not classifiable
<b>benzophenone (119-61-9)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
 STOT-single exposure : Not classified

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified  
 Viscosity, kinematic : No data available  
 Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
 Symptoms/effects after eye contact : Serious damage to eyes.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
LC50 fish 1	976 mg/l (OECD 203: Fish, Acute Toxicity Test, 72 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	45 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia sp., Static system, Fresh water, Experimental value)
ErC50 (algae)	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value)

<b>benzophenone (119-61-9)</b>	
EC50 Daphnia 1	0.27 mg/l (EC50; 24 h)
LC50 fish 2	15.3 mg/l (LC50; 96 h)

<b>TPO (75980-60-8)</b>	
LC50 fish 1	1 - 10 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 48 h; Oryzias latipes)
EC50 Daphnia 1	10 - 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
Threshold limit algae 1	> mg/l >10/100, EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Algae

<b>2-phenoxyethyl acrylate (48145-04-6)</b>	
LC50 fish 1	10 mg/l (Equivalent or similar to OECD 203, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	1.21 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	10 (≥ 0) mg/l

### 12.2. Persistence and degradability

<b>trimethylolpropane triacrylate, stabilized (15625-89-5)</b>	
Persistence and degradability	Biodegradability in water: no data available.
ThOD	1.835 g O <sub>2</sub> /g substance

<b>1,6-hexanediol diacrylate (13048-33-4)</b>	
Persistence and degradability	Inherently biodegradable.

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O <sub>2</sub> /g substance

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
Chemical oxygen demand (COD)	1.894 g O <sub>2</sub> /g substance
<b>benzophenone (119-61-9)</b>	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil.
BOD (% of ThOD)	0.12
<b>TPO (75980-60-8)</b>	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
<b>2-phenoxyethyl acrylate (48145-04-6)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>trimethylolpropane triacrylate, stabilized (15625-89-5)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>1,6-hexanediol diacrylate (13048-33-4)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
Log Pow	0.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>benzophenone (119-61-9)</b>	
BCF fish 1	3.4 - 12 (BCF)
Log Pow	3.18 - 3.38
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>TPO (75980-60-8)</b>	
BCF fish 1	< 40 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; Cyprinidae sp.)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>2-phenoxyethyl acrylate (48145-04-6)</b>	
Log Pow	2.58 (room temperature, Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)</b>	
Log Koc	1.099 - 1.1497 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>benzophenone (119-61-9)</b>	
Surface tension	0.042 N/m (50 °C)
<b>2-phenoxyethyl acrylate (48145-04-6)</b>	
Surface tension	53.6 mN/m (23 °C, Experimental value, 472.5 mg/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN3082 Environmentally hazardous substances, liquid, n.o.s., 9, III
UN-No.(DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s.
Class (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 171
Other information	: No supplementary information available.

#### Transportation of Dangerous Goods

Not applicable

#### Transport by sea

Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
---------------------------------------	---



# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG)	: 3082
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

### Air transport

Transport document description (IATA)	: UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
UN-No. (IATA)	: 3082
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s.
Class (IATA)	: 9 - Miscellaneous Dangerous Goods
Packing group (IATA)	: III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### trimethylolpropane triacrylate, stabilized (15625-89-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

#### 1,6-hexanediol diacrylate (13048-33-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### dipentaerythritol pentaacrylate (60506-81-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 1-ethenyl-2-pyrrolidinone, inhibited (88-12-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### benzophenone (119-61-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

#### (1-hydroxycyclohexyl)phenylmethanone (947-19-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### TPO (75980-60-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.

#### dichlorodimethylsilane, reaction products with silica (68611-44-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Oligomer- not GHS Classified

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 2-phenoxyethyl acrylate (48145-04-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

### 15.2. International regulations

#### benzophenone (119-61-9)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No	7000	7000 µg/day

benzophenone (119-61-9)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
toluene(108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
1-ethenyl-2-pyrrolidinone, inhibited(88-12-0)	U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date	: 01/09/2019
Other information	: Polymeric urges the customer receiving this safety data sheet to study it carefully to become aware of the hazards, if any, in the product. In the interest of safety, the customer should (1) notify your employees, agents and contractors of the information included in this SDS and (2) furnish a copy to each of your employees, customers and agents. Polymeric makes no warranty, express or implied, as to the accuracy or reliability of information contained herein, except that such information is, to the best of Polymeric's knowledge and belief, accurate as of the date indicated on this document. Final determination of suitability of material is the sole responsibility of the user. All the materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Full text of H-statements:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# SP Dry Erase Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*