

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : SP Shurfoot Anti-Slip
 Product code : 14343

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Polymeric US
 117 E. 14th Ave
 North Kansas City, MO 64116
 800-746-5567

1.4. Emergency telephone number

Emergency number Chemtel - U.S., Canada, Puerto Rico, U.S. Virgin Islands 1-800-255-3924; International 813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin sensitisation, Category 1 H317 May cause an allergic skin reaction.
 Hazardous to the aquatic environment — Acute Hazard, Category 3 H402 Harmful to aquatic life
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412 Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H317 - May cause an allergic skin reaction.
 H402 - Harmful to aquatic life
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS US) :

P261 - Avoid breathing vapours, spray, mist, fume.
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - If on skin: Wash with plenty of water
 P321 - Specific treatment (see supplemental first aid instruction on this label)
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-phenoxyethyl acrylate	(CAS-No.) 48145-04-6	15 - 30	Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,6-hexanediol diacrylate (Note D)	(CAS-No.) 13048-33-4	0.5 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
tripropylene glycol diacrylate	(CAS-No.) 42978-66-5	<= 1.56	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapour.
- Reactivity : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-phenoxyethyl acrylate (48145-04-6)
Not applicable

1,6-hexanediol diacrylate (13048-33-4)
Not applicable

tripropylene glycol diacrylate (42978-66-5)
Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Colorless, viscous liquid.

Colour : Colourless

Odour : acrylate odor

Odour threshold : No data available

pH : No data available

Melting point : Not applicable

Freezing point : No data available

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong bases. Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-phenoxyethyl acrylate (48145-04-6)	
LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral, 14 day(s))
tripropylene glycol diacrylate (42978-66-5)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, 14 day(s), Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

tripropylene glycol diacrylate (42978-66-5)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

2-phenoxyethyl acrylate (48145-04-6)	
LC50 fish 1	10 mg/l (Equivalent or similar to OECD 203, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	1.21 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	10 (≥ 0) mg/l

tripropylene glycol diacrylate (42978-66-5)	
LC50 fish 1	4.5 - 10 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	89 mg/l (EU Method C.1, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

2-phenoxyethyl acrylate (48145-04-6)	
Persistence and degradability	Not readily biodegradable in water.

1,6-hexanediol diacrylate (13048-33-4)	
Persistence and degradability	Inherently biodegradable.

tripropylene glycol diacrylate (42978-66-5)	
Persistence and degradability	Not readily biodegradable in water. Inherently biodegradable.

12.3. Bioaccumulative potential

2-phenoxyethyl acrylate (48145-04-6)	
Log Pow	2.58 (room temperature, Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1,6-hexanediol diacrylate (13048-33-4)	
Bioaccumulative potential	No bioaccumulation data available.

tripropylene glycol diacrylate (42978-66-5)	
Log Pow	2.77 (Experimental value, EU Method A.8: Partition Coefficient, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

2-phenoxyethyl acrylate (48145-04-6)	
Surface tension	53.6 mN/m (23 °C, Experimental value, 472.5 mg/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	No (test)data on mobility of the substance available.

tripropylene glycol diacrylate (42978-66-5)	
Log Koc	1 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	No (test)data on mobility of the substance available.

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-phenoxyethyl acrylate	CAS-No. 48145-04-6	10 - 30%
-------------------------	--------------------	----------

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/13/2019

Other information : Polymeric urges the customer receiving this safety data sheet to study it carefully to become aware of the hazards, if any, in the product. In the interest of safety, the customer should (1) notify your employees, agents and contractors of the information included in this SDS and (2) furnish a copy to each of your employees, customers and agents.

SP Shurfoot Anti-Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS US - Polymeric US

Polymeric US urges the customer receiving this safety data sheet to study it carefully to become aware of the hazards, if any, in the product. In the interest of safety, the customer should (1) notify your employees, agents and contractors of the information included in this SDS and (2) furnish a copy to each of your employees, customers and agents.

Polymeric US makes no warranty, express or implied, as to the accuracy or reliability of information contained herein, except that such information is, to the best of Polymeric US's knowledge and belief, accurate as of the date indicated on this document. Final determination of suitability of material is the sole responsibility of the user. All the materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.