

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Ultrabond WR
 Product code : WR Series

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Polymeric US
 117 E. 14th Ave
 North Kansas City, MO 64116
 800-746-5567

1.4. Emergency telephone number

Emergency number Chemtel - U.S., Canada, Puerto Rico, U.S. Virgin Islands 1-800-255-3924; International 813-248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 2	H225	Highly flammable liquid and vapour.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H361 - Suspected of damaging fertility or the unborn child.
 H401 - Toxic to aquatic life
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing vapours, spray, mist.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, eye protection.
 P302+P352 - If on skin: Wash with plenty of water/...
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P321 - Specific treatment (see supplemental first aid instruction on this label)
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.
 P370+P378 - In case of fire: Use media other than water to extinguish.
 P391 - Collect spillage.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-phenoxyethyl acrylate	(CAS-No.) 48145-04-6	15 - 30	Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
vinylcaprolactam	(CAS-No.) 2235-00-9	12.6 - 14	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
thfa	(CAS-No.) 75980-60-8	0.5 - 5	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
hydroxypropyl acrylate, mixed isomers (Note C)(Note D)	(CAS-No.) 25584-83-2	0.2 - 0.6	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317
1,6-hexanediol diacrylate (Note D)	(CAS-No.) 13048-33-4	0.19992 - 0.59976	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
epoxy resins, liquids, MM≤700	(CAS-No.) 25068-38-6	0 - 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapour.
- Reactivity : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

vinylcaprolactam (2235-00-9)		
Not applicable		
hydroxypropyl acrylate, mixed isomers (25584-83-2)		
ACGIH	ACGIH TWA (ppm)	0.5 ppm
1,6-hexanediol diacrylate (13048-33-4)		
Not applicable		
epoxy resins, liquids, MM≤700 (25068-38-6)		
Not applicable		
thfa (75980-60-8)		
Not applicable		
2-phenoxyethyl acrylate (48145-04-6)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: colors, varied
Odour	: acrylate odor
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

vinylcaprolactam (2235-00-9)	
LD50 oral rat	1114 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 400 mg/kg (Rabbit, Dermal)
ATE US (oral)	1114 mg/kg bodyweight
hydroxypropyl acrylate, mixed isomers (25584-83-2)	
ATE US (oral)	100 mg/kg bodyweight
ATE US (dermal)	300 mg/kg bodyweight
ATE US (vapours)	3 mg/l/4h
ATE US (dust,mist)	0.5 mg/l/4h
epoxy resins, liquids, MM≤700 (25068-38-6)	
LD50 oral rat	> 2000 mg/kg (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
thfa (75980-60-8)	
LD50 oral rat	> 2000 mg/kg (Rat; Literature)
2-phenoxyethyl acrylate (48145-04-6)	
LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral, 14 day(s))

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

hydroxypropyl acrylate, mixed isomers (25584-83-2)	
LC50 fish 1	10 - 22 mg/l (96 h, Leuciscus idus)
epoxy resins, liquids, MM≤700 (25068-38-6)	
LC50 fish 1	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1.1 - 2.8 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	> 11 mg/l (EPA 660/3 - 75/009, 72 h, Scenedesmus sp., Static system, Fresh water, Experimental value)
thfa (75980-60-8)	
LC50 fish 1	1 - 10 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 48 h; Oryzias latipes)
EC50 Daphnia 1	10 - 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
Threshold limit algae 1	> mg/l >10/100, EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Algae
2-phenoxyethyl acrylate (48145-04-6)	
LC50 fish 1	10 mg/l (Equivalent or similar to OECD 203, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	1.21 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	10 (≥ 0) mg/l

12.2. Persistence and degradability

vinylcaprolactam (2235-00-9)	
Persistence and degradability	Biodegradability in soil: no data available. Biodegradable in water.
hydroxypropyl acrylate, mixed isomers (25584-83-2)	
Persistence and degradability	Inherently biodegradable.
1,6-hexanediol diacrylate (13048-33-4)	
Persistence and degradability	Inherently biodegradable.
epoxy resins, liquids, MM≤700 (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water.
thfa (75980-60-8)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
2-phenoxyethyl acrylate (48145-04-6)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

vinylcaprolactam (2235-00-9)	
Bioaccumulative potential	No bioaccumulation data available.
hydroxypropyl acrylate, mixed isomers (25584-83-2)	
Bioaccumulative potential	No bioaccumulation data available.

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,6-hexanediol diacrylate (13048-33-4)	
Bioaccumulative potential	No bioaccumulation data available.
epoxy resins, liquids, MM≤700 (25068-38-6)	
BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)
Log Pow	2.64 - 3.78 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
thfa (75980-60-8)	
BCF fish 1	< 40 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; Cyprinidae sp.)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2-phenoxyethyl acrylate (48145-04-6)	
Log Pow	2.58 (room temperature, Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

epoxy resins, liquids, MM≤700 (25068-38-6)	
Surface tension	58.7 - 58.9 mN/m (20 °C, EU Method A.5: Surface tension)
Log Koc	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
2-phenoxyethyl acrylate (48145-04-6)	
Surface tension	53.6 mN/m (23 °C, Experimental value, 472.5 mg/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
 Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3082 Environmentally hazardous substances, liquid, n.o.s., 9, III
 UN-No.(DOT) : UN3082
 Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.
 Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
 Packing group (DOT) : III - Minor Danger
 Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



Dangerous for the environment : Yes

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
173 - An appropriate generic entry may be used for this material.
335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No limit
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number : 171
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
UN-No. (IMDG) : 3082
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

isopropylthioxanthone	CAS-No. 75081-21-9	0.5 - 10%
Oligomer- not GHS Classified	CAS-No.	10 - 30%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-phenoxyethyl acrylate	CAS-No. 48145-04-6	10 - 30%
-------------------------	--------------------	----------

epoxy resins, liquids, MM≤700 (25068-38-6)

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	---

thfa (75980-60-8)

EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.
--------------------------	--

2-benzyl-2-dimethylamino-4'-morpholinobutyrophenone (119313-12-1)

EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.
--------------------------	--

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/23/2019

Ultrabond WR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information

: Polymeric urges the customer receiving this safety data sheet to study it carefully to become aware of the hazards, if any, in the product. In the interest of safety, the customer should (1) notify your employees, agents and contractors of the information included in this SDS and (2) furnish a copy to each of your employees, customers and agents. Polymeric US makes no warranty, express or implied, as to the accuracy or reliability of information contained herein, except that such information is, to the best of Polymeric US's knowledge and belief, accurate as of the date indicated on this document. Final determination of suitability of material is the sole responsibility of the user. All the materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

SDS US - Polymeric US

Polymeric US urges the customer receiving this safety data sheet to study it carefully to become aware of the hazards, if any, in the product. In the interest of safety, the customer should (1) notify your employees, agents and contractors of the information included in this SDS and (2) furnish a copy to each of your employees, customers and agents.

Polymeric US makes no warranty, express or implied, as to the accuracy or reliability of information contained herein, except that such information is, to the best of Polymeric US's knowledge and belief, accurate as of the date indicated on this document. Final determination of suitability of material is the sole responsibility of the user. All the materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.