



Dye Sub Receptive Clear

Dye Sub Receptive Clear allows for Polymeric's dye sublimation inks to be applicable on white-coated metals. Dye Receptive Clear ensures vivid colors and durability.

ROLL COAT

Curing: 250 TO 300 MJ

Belt Speed: 300 @ 60FT

Coverage: 1500 TO 2000 SQ FT

Substrate WHITE COATED METAL

Start time and temp for dye sub

Temp 400 F

Time 60 seconds

A. Warranty Liability Limited to Purchase and Installation Costs

Notwithstanding anything provided herein or any other written material to the contrary, Polymeric only warrants the purchase price and costs of installation. POLYMERIC SHALL HAVE NO LIABILITY OR OBLIGATION TO ANY USER, BUYER, PURCHASER, DISTRIBUTOR OR OTHER PERSON OR ENTITY FOR ANY SPECIAL, DIRECT, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, HOWEVER CAUSED, INCLUDING WITHOUT LIMITATION, PERSONAL INJURY, LOSS OF BUSINESS, LOSS OF PROFIT, OR OTHER DAMAGE, whether or not buyer shall have informed Polymeric of the possibility or likelihood of any such damages.

B. Limitation of Implied Warranty and Fitness for a Particular Purpose

POLYMERIC'S WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO AN IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AN IMPLIED WARRANTY OF MERCHANTABILITY, AND ANY OTHER IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, PERFORMANCE, CUSTOMER USAGE OR TRADE.

C. A Pretest Prior to Production is Recommended to Ensure Proper Suitability for the Intended Application.

Polymeric US Inc.
117 E. 14th Avenue
N. Kansas City, MO. 64116